

ETS

CSM8 Speaker/Microphone

Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Description

Omni-directional pre-amplified microphone and 8 inch speaker for use in two way public address audio surveillance systems. Connects directly to our switcher / mixer / amplifiers or use one of our many interface products to make connections to DVRs or remote monitoring equipment.



Includes

- 1ea CSM8 Microphone/speaker.
- Installation instructions.

Wiring Requirements

- Microphone and speaker: 2 each stranded 22-gauge, 2-conductor shielded cables. 1000' max.

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning label in plain

CSM8 Microphone / Speaker

- Omni-directional element w/25' range.
- Low noise MOSFET pre-amplifier.
- Line level, unbalanced output.
- Adjustable gain.
- 200Hz-16Khz Frequency response.
- Microphone audio peak limiter (1second attack/release response time).
- Breakout circuit board on speaker with Euro-style connectors makes cable terminations fast and clean.
- 8" 5 watt speaker with 12.5" metal grill.
- Selectable .5w, 1w, 2w, 5w 70v line speaker power taps.
- Speaker frequency response: 200-10Khz.
-
- Dimensions: 12.5Dia x 3.5H.

Warranty

1 year parts and labor.

Made in USA