

ETS

Electronic Technical Services Inc.
211 Cochase SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Audio Surveillance Line Level to 70v Speaker Drivers

SA1 70V line Speaker Driver



Typically for use with remote monitoring 2-way audio surveillance systems. Can also be used in any single-zone public address application. Accepts a line level input and can drive a speaker up to 1000 feet away via a 70V line. Long cable runs must have the ETS LT870 transformer option installed at the speaker.

- Includes: RCA patch cord and 12VDC AC adapter.
- Switchable line type: 70V or 8 ohm direct
- Easy cable run termination.
- Power: 12VDC @ 100mA.
- Reverse polarity protected and fused.
- Dimensions: W 2.75 x L 4.38 x H 1.56.

SA4 4 Channel 70V Line Speaker Driver

Typically for use with multi-zone remote monitoring 2-way audio surveillance systems. Can also be used in any multi-zone public address application. Accepts line level inputs. Each output can drive a single speaker up to 1000 feet away via a 70V line. Long cable runs must have the ETS LT870 transformer option installed at the speaker.

- Includes: 4 RCA patch cords and 16.5Vac AC adapter.
- Switchable line type: 70V or 8 ohm direct.
- 2 Watt power capability.
- Frequency response 200-10kHz.
- Easy cable run termination.
- Power: 16.5Vac @ 500mA.
- Reverse polarity protected and fused.
- Dimensions: W 2.75 x L 4.38 x H 1.56.

