



Electronic Technical Services Inc.  
211 Conchas SE  
Albuquerque, NM 87123  
PH 505-888-3923 FAX 505-888-3926  
Website: www.etsnm.com


Sound Surveillance™

## ML1-WS Weather resistant, surface mount, un-pre-amplified microphone

### Description

The ML1-WS is a low cost, weather resistant omni-directional electret microphone for use with I/P cameras accepting **microphone level input** signals (PC compatible input). This product is suitable for OEM applications requiring an outdoor rated microphone. The microphone mounts in a standard 1/2" electrical knock out hole. The attached cord is 6' long and comes standard with a stereo 3.5mm connector on one end. The ML1-WS's 3.5mm connector can be removed and the cord can be directly connected to cameras with terminal blocks.

Note-camera must accept electret type microphone inputs.  
(camera supplies power to ECM cartridge)



### Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

Warranty 1 year parts and labor,

Made in USA

### ML1-WS Specifications

- Omni-directional pattern
- Max SPL 120db
- Frequency response: 20-18khz
- Sensitivity -50db
- 1.5-10Vdc operation
- 300-5k Ohm load resistance
- S/N 40db
- 3.5mm stereo connector
- 1/2" thick removable windscreen.
- Grey ABS plastic housing
- Mounts in a standard 1/2" electrical knock out hole.
- Weight: 0.050 lbs

### Includes:

- ML1-WS microphone.
- Warning label.
- Mounting locknut.

### Options:

Cord length 6'.  
Custom cable lengths up to 25' available.