



Sound Surveillance™

Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

SA1-MP 70V / 8 Ohm 10 Watt Speaker Driver

Description

The SA1-MP is a line level in to 10 Watt, selectable 70V or 8 Ohm speaker driver (power amplifier) typically for use in 2 way audio surveillance systems. Directly connects to DVRs and remote monitoring equipment. The SA1-MP. can also be used in any single zone public address application. Use one of our Sound Surveillance speakers with a built in 70V transformer to permit speaker cable runs up to 1000 feet



Includes

- SA1-MP Speaker driver.
- 16 VAC AC adapter.
- 1 each 3' RCA or 3.5mm patch cable.
- Installation instructions.

Options

- SPECIFY: RCA OR 3.5mm input connector.

Wiring Requirements

- Speaker cable run: stranded 22-gauge, 2-conductor:
- 70V mode: cable: 1000 feet max
- 8 Ohm mode: 100 feet max.

Warranty : 1 year parts and labor.

Made in USA

SA1-MP Speaker Driver Specifications

- RCA or 3.5mm input connector (specify upon ordering).
- Input: 70v line or 0dB (line level), switch selectable.
- Output: 8 Ohm direct or 70V, switch selectable.
- 10 Watts RMS output power.
- Output short circuit protected.
- Adjustable Volume level.
- Frequency response: 200-15Khz
- Fused, 16.5VAC power input.
- Compatible with all ETS STWx base stations
- Built in 70V 10w audio power transformer.
- Euro-style connectors makes speaker and microphone cable terminations fast and clean.
- Dimensions: L 5.3 x W 3.3 x H 1.6

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.