



Electronic Technical Services Inc.  
211 Conchas SE  
Albuquerque, NM 87123  
PH 505-888-3923 FAX 505-888-3926  
Website: www.etsnm.com

Sound Surveillance™

## SM1-SS-MS Omni-directional Pre-amplified Microphone With Mute Switch

### Description

High performance, Omni-directional, pre-amplified microphone for fixed location security applications. 25' pickup pattern in all directions. Built in limiter circuit automatically lowers the output level during loud sound intervals. Hi cut and low cut filters significantly reduce background noise. Built in mute switch turns audio output off) with LED indicator. LED lights red when muted and Green when not. Stainless steel plate mounts flush or on a single gang electrical box.



Connects directly to our switcher / mixer / amplifiers or use one of our many interface products to make fast and clean connections to DVRs or remote monitoring equipment.

### Includes:

- SM1-SS-MS flush mount microphone.
- Mounting screws.
- Warning label.
- Installation instructions.

### Wiring requirements:

2 conductor shielded (with drain wire) 22 gauge stranded. Max cable length 1500'

### Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

### Warranty

1 year parts and labor.

Made in USA

### SM1-SS-MS Specifications

- Omni-directional 25' pickup pattern.
- Low noise MOSFET pre-amplifier.
- 500Hz-13Khz Frequency response.
- Jumper selectable hi-cut/low-cut filters limit frequency response to 900-6khz significantly reducing background noise.
- Jumper selectable volume range:  
"Line level" (0db) or  
"Microphone level" (-30db)
- Adjustable gain in both volume ranges.
- 100 Ohm unbalanced output.
- Internal peak limiter circuit (.5 sec response)
- 3 position Euro-style connector makes cable termination fast and clean.
- Reverse polarity protected
- Power: 12 to 24VDC @ 20mA.
- On-board voltage regulator and RFI filtering.
- S/N ratio: more than 60DB
- Sensitivity -45DB
- Industrial temperature range -40 to 105C.
- Mute toggle switch
- Two color LED mute status indicator
- Stainless steel plate mounts flush or on a single gang electrical box.
- Dimensions: L 4.5" W 2.7" H 1.1"
- Weight .07lbs