



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

SM1 Omni-directional Pre-amplified Microphone

Description

High performance, Omni-directional, pre-amplified microphone for fixed location security applications. 25' pickup pattern in all directions. Built in limiter circuit automatically lowers the output level during loud sound intervals. Selectable Hi cut and low cut filters significantly reduce background noise. Flexible plastic plate mounts flush or on a single gang electrical box.

Connects directly to our switcher / mixer / amplifiers or use one of our many interface products to make fast and clean connections to DVRs or remote monitoring equipment.



Includes:

- SM1 flush mount microphone.
- Mounting screws.
- Warning label.
- Installation instructions.

Wiring requirements:

2 conductor shielded (with drain wire) 22 gauge stranded. Max cable length 1500'

Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

Warranty

1 year parts and labor.

SM1 Specifications

- Omni-directional 25' pickup pattern.
- Low noise MOSFET pre-amplifier.
- 500Hz-13KHz Frequency response.
- Jumper selectable hi-cut/low-cut filters limit frequency response to 900-6khz significantly reducing background noise.
- Jumper selectable volume range:
"Line level" (0db) or
"Microphone level" (-30db)
- Adjustable gain in both volume ranges.
- 100 Ohm unbalanced output.
- Internal peak limiter circuit (.5 sec response)
- 3 position Euro-style connector makes cable termination fast and clean.
- Reverse polarity protected
- Power: 12 to 24VDC @ 10mA.
- On-board voltage regulator and RFI filtering.
- S/N ratio: more than 60DB
- Sensitivity -45DB
- Industrial temperature range -40 to 105C.
- Flexible plastic plate mounts flush or on a single gang electrical box.
- Dimensions: L 4.7" x W 2.9" H 0.9"
- Weight .03lbs