



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926

Sound Surveillance™

SM2-CP Ext 12-24Vdc Input, DVR / IP Camera Microphone Interface Adapter

Description

The SM2-CP is a SM1 series microphone interface designed to be used with IP cameras that are powered by 12-24vdc. The SM2-CP can also be used in any application that has a 12-24v power source available such as in automotive applications. The SM2-CP features a transformer isolated audio output for prevention of ground loops. The SM2-CP also features an output volume control and an unbalanced line level output.



Includes

- SM2-CP Interface adapter.
- 1 each 3' RCA , 3.5mm or flying leads patch cable (please specify).
- Installation instructions.

Options

- SPECIFY: RCA, 3.5mm, or Flying leads output cable.

Wiring Requirements

- Microphone cable run: Stranded 22-gauge, 2-conductor shielded cable. Distances up to 1500 feet.

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.

SM2-CP Interface Adapter Specifications

- RCA, 3.5mm jack of flying leads for connection to DVRs etc.
- Line level (0db) output level.
- Adjustable output level
- Transformer isolated audio output eliminates ground loops and noise.
- Terminal block connectors makes cable terminations fast and clean.
- LED power indicator.
- Power: 12-24 VDC @ 10mA
- Reverse polarity protected.
- All power circuitry and cable run protected with auto-reset type fuse.
- Black plastic ABS housing.
- Weight .06lbs
- Dimensions: L 2.7 x W 1.7 x H 1.6

Warranty : 1 year parts and labor.

Made in USA