

ETS

Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

SM6 Audio Surveillance Kit

Description

Complete single zone audio surveillance system. Can be used independently for monitoring live audio or with tape recorders or DVRs for recording and playback.



Kit Includes

- SM1 Pre-amplified microphone.
- SM1 Mounting screws
- SM3 Amplifier
- 12 VDC AC adapter.
- 3' Dual RCA Patch cable.
- Warning label.

Options

- RM1, RM2, RM3 18" Rack mounts.

Wiring Requirements

- Stranded 22-gauge, 2-conductor shielded cable with drain wire.
Max. cable length: 1500'

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning label in plain view is all that is required.

Warranty

1 year parts and labor.

Made in U.S.A.

SM1 Microphone Specifications

- Omni-directional Electret element.
25' range in all directions.
- Low noise MOSFET pre-amplifier.
- Line level, unbalanced output.
- Adjustable gain.
- Treble boost circuit. Selectable on/off.
Enhances clarity of time lapse recordings.
- Limiter circuit. Selectable on/off.
- 3 position Euro-style connector makes cable termination fast and clean.
- Flush mountable. Can be mounted on a single gang electrical box.
- Power: 12 VDC @ 10mA.
- See SM1 data sheet for more information.

SM3 Amplifier Specifications

- Standard RCA jacks for connection to tape recorders, DVRs, etc.
- 3 position Euro-style connector makes cable termination fast and clean.
- 1 Watt Power amplifier.
- 3" full range speaker.
- Tape monitor switch.
- 3.5mm Headphone jack.
- Power: 12 VDC @ 250mA.
- Reverse polarity protected and fused.
- Dimensions L 5.4 x W 4.1 x H 1.5
- See SM3 data sheet for more information.