



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

SMEA-1 IP PoE Camera Interface Box

Description

In line adaptor for tapping power off Ethernet powered I/P cameras to supply power to ETS Sound Surveillance microphones, accessories and breakout box for terminating the microphone to the "microphone" or "line input" of IP cameras. Supports both modes A and B of IEEE802.3af.

For use with ETS
or Louroe microphones only



Includes:

- SMEA-1 Interface
- Includes: One 6' 3.5mm patch cord (or specify RCA or "flying leads")
- Installation instructions.

Microphone wiring requirements:

2 conductor shielded (with drain wire) 22 gauge stranded. Max cable length 1500'

Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

Warranty

1 year parts and labor.

Made in USA

SMEA-1 Specifications

- RCA or 3.5mm audio output connector
- Microphone or line level output.
- Transformer isolated audio output.
- Adjustable audio output level.
- Euro-style connector makes cable termination of microphone fast and clean.
- RJ45 Ethernet in/out jacks
- Straight through CAT5 connections (no crossover)
- A/B mode switch for IEEE802.3af power format.
- Internal regulator converts PoE 48-57Vdc to 15Vdc @ 30ma for powering accessories and/or multiple microphones.
- current consumption 15ma.
- Led power indicator
- Auto polarity protected & fused.
- Operating Temperature 0 to 70C
- Dimensions: L 3.3 x W 2.0 x H 1.6