



Sound Surveillance™

Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

STWI-2 Two channel Speaker/Microphone Interface

Description

The STWI-2 is a dual channel, passive (no electronics) DVR and I/P camera interface for use with standard STW1 series speaker/microphones. It provides easy termination (breakout) of field cable runs, power input, and input/output of audio signals to 3.5mm or RCA output jacks.



Includes

- STWI-2 Interface adapter.
- 12 VDC 500ma AC adapter.
- 4 each 3' RCA or 3.5mm patch cables.
- Installation instructions.

Options

- SPECIFY: RCA OR 3.5mm output connectors.

Wiring Requirements

- 4ea, Stranded 22-gauge, 2-conductor shielded cable. 1000' max.

Warranty : 1 year parts and labor.

Made in USA

STWI-2 Interface Specifications

- Standard RCA or 3.5mm jacks for connection to DVRs etc.
- Line level audio input/output.
- Euro-style connectors makes cable terminations fast and clean.
- Power: 12VDC @ 500mA.
- Reverse polarity protected and fused.
- Dimensions: L 4.3x W 2.7 x H 1.6.

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.