

ETS

Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

TELCO-AD1 Single channel unshielded cabling adaptor

Description

The TELCO-AD1 adaptor set is used to convert all Sound Surveillance product inputs and outputs for use with unshielded cable runs or for use with spare conductors available in telephone systems.



Includes

- 2 ea. CAT5-AD1 adaptor
- Installation instructions

Wiring requirements:

- 3 conductors for connections to Sound Surveillance products (2 conductor shielded for distances over 10' recommended).
- 4 conductor 24 gauge (minimum) 500 feet max.

Warranty 1 year parts and labor.

Made in USA

TELCO-AD1 Features and Specifications

- Euro-style connectors for simple interface between the TELCOM-AD1 and all Sound Surveillance product inputs and outputs.
- Euro-style connectors for fast connections to cable run ends or interface between telephone system punch down blocks.
- Converts our standard unbalanced audio signals to balanced audio at 500 Ohms impedance permitting the use of unshielded cable runs.
- Use with all one and two way Sound Surveillance products (two TELCO-AD1 sets required for two way applications)
- Max cable run 500 feet.
- Double stick tape mounting.
- Dimensions: L 1.75 x W .75 x H .75