



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

EEM-1 High Performance Substitute for Eagle 2107/2102P Microphone.

Description

The EEM-1 is a high performance substitute for the Eagle 2107/2102P microphone. It features higher sensitivity, adjustable gain and adjustable high cut and low cut filters. The EEM-1 also has lower distortion and higher gain and S/N ratio than the Eagle 2107/2102P.



Includes:

- EEM-1 Microphone
- Warning label.
- Installation instructions.

Wiring requirements:

2 conductor shielded (with drain wire) 22 gauge stranded. Max cable length 500'.

Options:

- Ultra low noise, higher sensitivity microphone capsule. Add -LN to Part number
- The EEM-1 is available in many other form factors. Contact sales1@etsnm.com for further information

Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

EEM-1 Specifications

- Low noise MOSFET pre-amplifier
- Omni-directional 25' pickup pattern
- 100Hz-16Khz Frequency response.
- Adjustable lo-cut filter: (100hz to 1Khz)
- Adjustable hi-cut filter: (5Khz to 16Kz)
- Transient protected output.
- 12v Eagle phantom power
- S/N ratio: 60DB
- Sensitivity -44db
- Temperature range -25 to 85C.
- Conformal coated PCB
- RFI filtering.
- White single gang plate
- Dimensions: L 4.7" x W 2.9" H 0.9"
- Weight .1lbs

Warranty

1 year parts and labor.

Made in USA