211 Conchas SE Albuquerque, NM 87123 PH 505-888-3923 FAX 505-888-3926

Website: www.etsnm.com

Sound Surveillance tm

ML1-PH Pin Hole Omni-directional Microphone

Description

The ML1-PH is a pin hole, covert, high performance, low cost omni-directional electret microphone for use with IP cameras accepting microphone level input signals (PC compatible input). The ML1-PH is designed to be mounted on the top side of ceiling tiles or drywall and peer through a tiny hole made with a counter sink drill bit. Add -FL to the P/N for a flying lead output for connections to cameras with terminal blocks.

For use with IP cameras accepting microphone level inputs (the camera supplies power to ECM cartridge)



0.60 0.15 8 .100 THICK DISK 3.5MM STEREO CONNECTOR 6' PVC CABLE + IS TIP AND RING - IS SLEEVE

Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

Warranty 1 year parts and labor,

Made in USA

ML1-PH Specifications

- Omni-directional pattern
- Max SPL 120db
- Frequency response: 40-17khz
- Sensitivity -44db
- -40db output (mic level)
- 2-10Vdc operation
- 2-5k Ohm load resistance
- S/N 60db
- 6' standard cable length
- 3.5mm stereo connector
- Black Anodized aluminum parts
- Operating temperature -40 to 85C
- Weight: 0.025 kg

Includes

- ML1-PH microphone.
- Mounting Disk
- Warning label.

Options

- Cable lengths of up to 25' are available. Add –XX to P/N where XX = number of feet
- Add -FL to P/N for flying lead output
- Add -LN to P/N for higher performance capsule