



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

MPI-1P Microphone Pre-amplifier

Description

The MPI-1P is a high performance microphone pre-amplifier designed to be used with any of our ML1 series microphones. It features adjustable Hi and Lo cut filters and an adjustable automatic gain control. The output of the MPI-1 is designed to be connected to directly to DVRs, audio recorders, etc.



Includes:

- MPI-1P Pre-amplifier
- 15Vdc, power supply
- 3.5mm patch cord
- Installation instructions.

Option (add to P/N):

- 3.5mm for 3.5mm ended patch cord
- RCA for RCA ended patch cord
- FL for flying lead ended patch cord

Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

Warranty

1 year parts and labor.

Made in USA

MPI-1P Specifications

- Low noise MOSFET pre-amplifier.
- 200Hz-16Khz Frequency response (hi-cut and lo-cut off)
- Adjustable lo-cut filter: (200hz to 1Khz)
- Adjustable hi-cut filter: (5Khz to 16Kz)
- Adjustable automatic gain control. (compression range 1:1-10:1).
- Switch selectable volume range: "Line level" (0db) or "Microphone level" (-30db)
- Adjustable output level (post AGC).
- 100 Ohm unbalanced output.
- Treble boost pre-emphasis.
- Fused and polarity protected power input
- 2.1mm x 5.5mm barrel power in tip -.
- Power: 15vdc @15mA.
- On-board voltage regulators and RFI filtering.
- Temperature range -25C to 85C.
- Black plastic ABS housing.
- Dimensions: L 3.3 x W 2.0 x H 1.6
- Weight .05lbs