



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™


PM1-WPCF Compact Weather Proof (IP67), Balanced Output, 12-48Vdc Phantom Powered Microphone

Description

The PM1-WPCF is a professional grade, compact weather proof (IP67), Electret, Omni-directional, microphone for use with professional audio mixing consoles, surveillance equipment and other devices that support 12 to 48vdc phantom powered, balanced output microphones.

Compatible with these ETS Interfaces:

PMI-1
PMI-4
SMEA-1P
PACEQ-1



Includes:

PM1-WPCF microphone
Warning label.
Installation instructions.

Wiring requirements:

Microphone output: 2 conductor shielded (with drain wire) 22 gauge stranded. Max cable length 500'

Ordering Options:

PM1-WPCF-XX XX = length of outdoor rated UV resistant cable.

Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

Warranty 1 year parts and labor.

Made in USA

PM1-WPCF Specifications

Electret microphone element
Omni-directional pickup pattern
Balanced output
12V-48V Phantom power input
Current consumption: 6ma @ 48vdc
2ma @ 12vdc
Low cut filter switch
Frequency response:
Low cut out: 50-16Khz
Low cut in 500-16Khz
S/N ratio more than 60db
Sensitivity -45db
Low noise, balanced line driver
Output impedance 500 Ohms
Built in RFI filtering
Potted electronics
6' UV rated outdoor cable whip. Custom lengths available.
Operating temperature -25C to 70C
Weight: .13 lbs
Directly surface mountable
Grey powder coated cast aluminum single gang base.
Dimensions: L 2.8" x W 2.17" H 1.0"