


## PM1 Flush Mount, Balanced Output, 12-48Vdc Phantom Powered Microphone

### Description

The PM1 is a professional grade, flush mount, Omni-directional, Electret microphone for use with professional audio mixing consoles, surveillance equipment and other devices that support 12 to 48vdc phantom powered, balanced output microphones.

Compatible with these ETS Interfaces:

PMI-1  
PMI-4  
SMEA-1P  
PACEQ-1



### Includes:

- PM1 microphone
- Mounting screws.
- Warning label.
- Installation instructions.

### Wiring requirements:

Microphone output: 2 conductor shielded (with drain wire) 22 gauge stranded. Max cable length 500'

### Ordering Options:

- PM1-LN Low noise high sensitivity microphone capsule.
- PM1-BK Black ABS plastic plate.

### Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

### PM1 Specifications

- Electret microphone element
- Omni-directional pickup pattern
- Balanced output
- 12V-48V Phantom power input
- Current consumption: 6ma @ 48vdc  
2ma @ 12vdc
- Low cut filter switch
- Frequency response:  
Low cut out: 50-16Khz  
Low cut in 500-16Khz
- S/N ratio more than 60db (80db LN option)
- Sensitivity -45db (-28db LN option)
- Low noise, balanced line driver
- Output impedance 500 Ohms
- Built in RFI filtering
- 3 position Euro-style connector makes cable termination fast and clean.
- Operating temperature -25C to 70C
- Weight: .05lbs
- Bright white ABS plastic plate
- Dimensions: L 4.7" x W 2.9" H 0.9"

Warranty 1 year parts and labor.

Made in USA