



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

PMI-1U USB Microphone PC interface for ETS PM1 series and any other balanced mic

Description

The PMI-1U Microphone PC interface is for use with ETS PM1 series microphones or electret and dynamic professional balanced microphones. Features include adjustable gain in two ranges, adjustable low cut filter and Mute switch with indicator. Also features Internal DC-DC converter for powering Electret mics without the need for an external power supply.



Includes

- PMI-1U Interface box
- 6' USB cord
- Installation instruction

Wiring Requirements

Microphone cable run: Stranded 22-gauge, 2-conductor shielded cable or high grade "microphone" cable. Distances up to 500 feet.

Warranty

1 year parts and labor.

Made in USA

PMI-1U Interface Specifications

- Ultra low noise microphone pre-amplifier
- Microphone pre-amp gain range and volume control
- Input impedance 1K Ohms.
- XLR and terminal block microphone input
- Input: RFI and transient protected
- Internal DC-DC converter steps up USB 5v to 48v regulated phantom power.
- No external power source required
- Phantom power on/off switch
- Low cut filter variable from 20-150hz
- Mute switch with indicator
- Outputs short circuit protected.
- USB output
- Frequency response 20HZ-20khz (low cut out)
- Power consumption, 200ma max@5Vdc.
- Power indicator
- Dimensions: L 4.2 x W 2.7 x H 1.6
- Weight: .12kg