



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

SMI-2 Two Channel Microphone Interface Adaptor

Description

Powers up to 2 ETS SM1 series microphones and distributes their audio outputs to individual RCA (or optional 3.5mm) jacks. Designed for connecting SM1 series microphones to equipment with un-balanced, line level inputs. Ideal for use with DRVs, remote monitoring equipment and multiple CCTV monitors (with built in speakers).



Includes

- SMI-2 Interface adapter.
- 15 VDC 800ma AC adapter.
- 2 each 6' RCA or 3.5mm patch cables.
- Installation instructions.

Options:

- Add -RCA or -FL (Flying Leads) to P/N for alternate output cables.

Wiring Requirements

- Microphone cable runs: Stranded 22-gauge, 2-conductor shielded cable. Distances up to 1000 feet each.

Warranty : 1 year parts and labor.

Made in USA

SMI-2 Interface Adapter Specifications

- RCA output jacks.
- Line level (0db) output levels.
- Terminal block microphone connections.
- LED power indicator.
- Power: 12 VDC @ 20mA
- Reverse polarity protected.
- PPTC fused.
- Black plastic ABS housing.
- Dimensions: L 3.3 x W 2.0 x H 1.6
- Weight .07kg

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.