



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

SA1-MP 40W 8 Ohm / 10W 70V Speaker Driver

Description

The SA1-MP is a line level input speaker driver which can power a 8 Ohm speaker at 40Watts or a 70v speaker(s) at 10 Watts. For use in PA talk down applications. Connects to DVRs, IP cameras and remote monitoring equipment. Use one of our Sound Surveillance speakers with a built in 70V transformer to permit speaker cable runs up to 500 feet



Includes

- SA1-MP Speaker driver.
- 24Vdc 2A AC adapter.
- 1 each 6' RCA patch cord
- Installation instructions.

Options

- Add -3.5MM or -FL (Flying Leads) to P/N for alternate output cables.

Wiring Requirements

- Speaker cable run: stranded 22-gauge, 2-conductor:
- 70V mode: cable: 500 feet max
- 8 Ohm mode: 100 feet max.

Warranty : 1 year parts and labor.

Made in USA

SA1-MP Speaker Driver Specifications

- RCA input jack
- Input: 70v line or 0dB (line level), switch selectable.
- Output: 8 Ohm direct at 40 Watts or 70V at 10 Watts, switch selectable.
- Output short circuit protected.
- Gain range switch
- Adjustable Volume level.
- Frequency response: 200-15Khz
- PTTTC fused power input.
Power 24Vdc @ 2A
- Built in 70V 10w audio power transformer.
- Terminal block speaker connections.
- Dimensions: L 5.3 x W 3.3 x H 1.6
- Weight .35kg

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.