

Electronic Technical Services Inc. 211 Conchas SE Albuquerque, NM 87123 PH 505-888-3923 FAX 505-888-3926

Website: www.etsnm.com

Sound Surveillance tm

SA4-LP Four Channel 70V / 8 Ohm Speaker Driver

Description

The SA4-LP is a 4 channel, line level in to 2 Watt, selectable 70V or 8 Ohm speaker driver Connects to DVRs and remote monitoring equipment. The SA4-LP can also be used in any four zone public address application. Use our Sound Surveillance speakers with a built in 70V transformers to permit speaker cable runs up to 1000 feet.



Includes

- SA4-LP Speaker driver.
- 15Vdc 800ma AC adapter.
- 4 each 6' RCA patch cords
- Installation instructions.

Options

 Add –3.5MM or –FL (Flying Leads) to P/N for alternate output cables.

Wiring Requirements

- Speaker cable runs: stranded 22gauge, 2-conductor:
- 70V mode: 1000 feet max each run.
- 8 Ohm mode: 20 feet max each run.

SA4-LP Speaker Driver Specifications

- Line level (0db) audio inputs.
- RCA input jacks. connection to DVRs etc.
- Adjustable Volume controls.
- Selectable 70V or 8 Ohm output levels.
- 2.5 Watts RMS power output @ 200-10Khz.
- Terminal block speaker connections.
- LED power indicator.
- Power:12Vdc @ 800mA max
- · Reverse polarity protected.
- PPTC fused.
- Black plastic ABS housing.
- Dimensions: L 4.2 x W 2.7 x H 1.6
- Weight .27kg

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.