



**Electronic Technical Services Inc.**  
211 Conchas SE  
Albuquerque, NM 87123  
PH 505-888-3923 FAX 505-888-3926  
Website: www.etsnm.com

**Sound Surveillance™**

# SM1-PA Microphone Pre-amplifier

## Description

The SM1-PA is a microphone pre-amplifier designed to be used with any of our ML1 series microphones. It features a 12-24vdc power input, hi and lo cut filters and an adjustable gain control. The output of the SM1-PA is designed to be connected directly to ETS base stations, interfaces and other equipment.



## Includes:

- SM1-PA Pre-amplifier
- Installation instructions.

## Wiring requirements:

2 conductor shielded (with drain wire) 22 gauge stranded. Max cable length 1000'.

## Caution

*It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.*

## Warranty

1 year parts and labor.

Made in USA

## SM1-PA Specifications

- Low noise MOSFET pre-amplifier.
- 500Hz-13Khz Frequency response.
- Switchs electable hi-cut/low-cut filters limit frequency response to 900-6khz significantly reducing background noise.
- Switch selectable volume range:  
"Line level" (0db) or  
"Microphone level" (-30db)
- Adjustable gain in both volume ranges.
- 100 Ohm unbalanced output.
- Internal peak limiter circuit (.5 sec response)
- 3 position terminal block microphone connection.
- Reverse polarity protected
- Power: 12 to 24VDC @ 10mA.
- On-board voltage regulator and RFI filtering.
- Temperature range -25C to 85C.
- Black plastic ABS housing.
- Dimensions: L 2.7 x W 1.7 x H 1.6
- Weight .05kg