



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

SMA1-HPC5 Speaker Driver Microphone Interface

Description

The SMA1-HPC5 is a line level, 30 Watt, 70V speaker driver (power amplifier) and SM series microphone interface typically for use in 2 way audio surveillance systems. A single CAT5 cable connects the SMA1-HPC5 to any ETS speaker/microphone ordered with a C5 option. Directly connects to DVRs and remote monitoring equipment.



Includes

- SMA1-HPC5 Speaker driver / microphone interface.
- 24 VAC 50VA AC adapter.
- 2 each 6' RCA patch cord
- Installation instructions.

Options

- Add -3.5MM or -FL (Flying Leads) to P/N for alternate output cables.

Wiring Requirements

- 1 CAT5 8 conductor cable and 2 each RJ45 connectors. 250' max.

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.

SMA1-HPC5 Speaker/Mic. interface

- Single CAT5 cable run up to 250' between SMA1-HPC5 and speaker/microphone.
- Line level (0db) audio input and outputs.
- Standard RCA or 3.5mm jacks for connection to DVRs etc.
- Adjustable volume controls for speaker and microphone.
- 30 Watts RMS power output (70v balanced line).
- Short circuit protected.
- Built in 70V 30w audio power transformer.
- 2 position terminal block for call switch
- LED power indicator and PPTC fused.
- Call sw: unreferenced, 2 free terminals.
- Power:24 VAC @ 2000mA
- Grey plastic ABS housing.
- Dimensions: L 7.0 x W 4.5 x H 3.75
- Weight 1.25kg

Warranty : 1 year parts and labor.

Made in USA