

Electronic Technical Services Inc. 211 Conchas SE Albuquerque NM 87123

Albuquerque, NM 87123 PH 505-888-3923 FAX 505-888-3926 Website: www.etsnm.com Sound Surveillance tm

SMA1-LPEA PoE IP Camera Speaker / Microphone Interface Box

Description

Two-way audio In line adaptor for tapping power off Ethernet powered IP cameras to supply power to ETS Sound Surveillance speaker / microphones. Built-in 2.5W speaker power amplifier and terminal blocks for connecting ETS SM1 series microphones and 8 Ohm or 70V speakers. 3.5mm (or RCA) input / output jacks for connections to "microphone" / "line input" and "line output" of IP cameras. Supports both modes A and B of IEEE802.3af.



Includes:

- SMA1-LPEA interface
- 2ea. 6' 3.5mm patch cords.
- Installation instructions.

Options:

 Add –RCA or –FL (Flying Leads) to P/N for alternate output cables.

Wiring requirements:

2 conductor shielded (with drain wire) 22 gauge stranded. Max cable lengths 500'

Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

SMA1-LPEA Specifications

- RCA or 3.5mm audio input / output connectors
- Microphone or line level output.
- Speaker line level audio input.
- Transformer isolated audio input and output.
- Adjustable audio input / output levels.
- 2.5 Watt speaker power amplifier.
- Selectable gain range for speaker
- Selectable speaker output: 70V or 8 ohm.
- RJ45 in/out jacks for Ethernet.
- Straight through CAT5 connections (no crossover)
- A/B mode switch for IEE802.3af power format.
- Internal switching regulator converts PoE 48-57Vdc to 15Vdc for internal speaker power amplifier and microphone power supply.
- Current consumption 150ma. Maximum
- Led power indicator.
- 3 position terminal blocks for speaker and microphone.
- PPTC protected.
- Operating Temperature 0 to 70C
- Dimensions: L 5.3 x W 3.3 x H 1.6
- Weight .16kg