



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

SMA1-MPC5 10W 70V Speaker Driver Microphone interface with CAT5 connections

Description

The SMA1-MPC5 is a line level input speaker /microphone interface with a 10 Watt speaker driver. A single CAT5 cable connects the SMA1-MPC5 to any ETS speaker / microphone with the -C5 option. For use in two-way PA talk down applications. Connects to DVRs, IP cameras and remote monitoring equipment.



Includes

- SMA1-MPC5 Speaker /mic interface.
- 24Vdc 2A AC adapter.
- 2 each 6' RCA patch cord
- Installation instructions.

Options

- Add -3.5MM or -FL (Flying Leads) to P/N for alternate output cables.

Wiring Requirements

- Speaker/microphone connection:
CAT5/6 cable 500 feet max

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.

SMA1-MPC5 Specifications

- RCA audio input output jacks
- Single CAT5/6 cable connects SMA1-MPC5 to any ETS -C5 optioned speaker /microphone.
- Output short circuit protected.
- Gain range switch for speaker
- Adjustable Volume levels for speaker and microphone.
- PTTC fused power input.
Power 24Vdc @ 1.5A
- Built in 70V 10w audio power transformer.
- Terminal block speaker and microphone connections.
- Dimensions: L 5.3 x W 3.3 x H 1.6
- Weight .35kg

Warranty : 1 year parts and labor.

Made in USA