



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

SMI-1CP Ext 12-24Vdc Input, DVR / IP Camera Microphone Interface Adapter

Description

The SMI-1CP is a SM1 series microphone interface designed to be used with IP cameras that are powered by 12-24vdc. The SMI-1CP can also be used in any application that has a 12-24v power source available such as in automotive applications. The SMI-1CP features a transformer isolated audio output for prevention of ground loops. The SMI-1CP also features an output volume control and an unbalanced line level output.



Includes

- SMI-1CP Interface adapter.
- 1 each 3' RCA , 3.5mm or flying leads patch cable (please specify).
- Installation instructions.

Options:

- Add -RCA or -FL (Flying Leads) to P/N for alternate output cables.

Wiring Requirements

- Microphone cable run: Stranded 22-gauge, 2-conductor shielded cable. Distances up to 1000 feet.

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.

SMI-1CP Specifications

- 3.5mm output jack
- Line level (0db) output level.
- Adjustable output level
- Transformer isolated audio output eliminates ground loops and noise.
- 3 position terminal block microphone connection.
- LED power indicator.
- Power: 12-24 VDC @ 10mA
- Reverse polarity protected.
- All power circuitry and cable run PPTC fused.
- Black plastic ABS housing.
- Dimensions: L 2.7 x W 1.7 x H 1.6
- Weight .06kg

Warranty : 1 year parts and labor.

Made in USA