



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

HSM11-D High Performance Weather Proof Speaker Microphone

Description

Weather resistant, Indoor/outdoor, Omni-directional pre-amplified microphone and 70V 30W, 11X7 Inch square horn speaker for use in two way public address audio surveillance systems. The HSM8D's microphone is concealed in the speaker sound chamber which protects the microphone from weather and converts the microphone into a directional pattern pickup with -12db attenuation (at 90 degrees) on all sides. Locating the microphone in the Speaker's sound chamber also lowers the overall cost of the unit.



Includes

- HSM11-D Speaker microphone
- Installation instructions

Microphone / speaker wiring Requirements

- 2 each, Stranded 22-gauge, 2-conductor shielded cables with drain wires. Max. cable length: 500'

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning label in plain view is all that is required.

HSM11-D Specifications

- Omni-directional 25' directional pickup pattern
- Excellent wind noise suppression
- Low noise MOSFET pre-amplifier.
- 500Hz-16Khz Frequency response (hi-cut and lo-cut off)
- 100 Ohm unbalanced output.
- Treble boost pre-emphasis.
- S/N ratio: more than 60DB (80db -LN option)
- Sensitivity -45DB (-28db -LN option)
- Power: 12-24Vdc @ 10ma
- Reverse polarity protected and fused.
- 70v 30W speaker
- IP 54 rated
- ABS enclosure
- Weather proof connection box.
- Dimensions: 11x7Horn x L11.
- Temperature range: -20 to 70C
- Weight .95kg

Warranty

1 year parts and labor.

Made in U.S.A.