




Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

SMI5 4 Channel Audio Surveillance kit

Description

4 zone audio surveillance kit designed to connect to audio recorders, CCTV monitors (with built in speakers), video recorders, DVRs, remote monitoring equipment, etc.



Includes

- 4 SM1 Pre-amplified microphones
- SMI4 Interface adapter.
- SM1 mounting screws
- 15 Vdc 800ma AC adapter.
- 4 6' RCA or 3.5mm Patch cables.
- 4 ETS warning labels
- Installation Instructions.

Options

- SPECIFY: RCA output connectors OR 3.5mm when ordering.

Wiring Requirements

- Stranded 22-gauge, 2-conductor shielded cable w/drain wire.
Max. cable length per mic. 1000'

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.

Warranty

1 year parts and labor.

Made in U.S.A.

SM1 Microphone Specifications

- Omni-directional Electret element.
25' range in all directions.
- Frequency response: 350-12Khz.
- Low noise MOSFET pre-amplifier.
- Line level, unbalanced output.
- Internal peak limiter circuit (.5 sec response)
- Adjustable gain.
- Hi/Lo volume range switch
- Hi and Low cut filter switches
- 3 position terminal block
- Flush mountable. Can also be mounted on a single gang electrical box.
- Power: 12-24VDC @ 10mA
- See SM1 data sheet for more information

SMI4 Interface Adapter Specifications

- RCA or 3.5mm jacks for connection to DVRs, Remote monitoring equipment, etc.
- 3 position terminal block microphone connections.
- LED power indicator.
- Power: 12 VDC @ 40mA
- Reverse polarity protected and fused.
- Dimensions: L 4.2 x W 2.7 x H 1.6
- See SMI4 data sheet for more information.